



PTFE Tape TF-W27

self adhesive

acc. to ABS 5766 A



Applications	sliding assistance and surface protection
Material	Polytetrafluorethylene, specially coated, meets the requirements of ABS 5766 A
Colour	grey
Dimensions, width ¹⁾	from 25 mm up to 1200 mm
Dimension, roll length ¹⁾	min. 2.5 m
Thickness ¹⁾	0.35 mm, 0.65 mm, 1.0 mm
Peel resistance on CRES	>20 N/25 mm
Temperature range	-55 °C up to +85 °C
Storage Temperature	from -10 °C to 25 °C
Shelf Life	12 months
Flammability	meets the requirements of FAR 25.853(a)(1)(ii), Test acc. to AITM 2.0002 B
1) Other dimensions and thicknesses are available on request.	



PTFE Tape TF-W29

self adhesive

acc. to ABS 5766 B



Applications:	sliding assistance and surface protection
Material	Polytetrafluorethylene, specially coated, meets the requirements of ABS 5766 B
Colour	grey
Dimensions, width ¹⁾	from 15 mm up to 300 mm
Dimension, roll length ¹⁾	min. 2.5 m
Thickness ¹⁾	0.15 mm, 0.30 mm, 0.55 mm
Peel resistance on CRES	>7 N/25 mm
Temperature range	-55 °C up to +150 °C
Storage Temperature	from -10 °C to 25 °C
Shelf Life	6 months
Flammability	meets the requirements of FAR 25.853(a)(1)(ii), Test acc. to AITM 2.0002 B
1) Other dimensions and thicknesses are available on request.	